

Combine Demolition Derby
Yellow Medicine County Fair
Friday, July 29th 2011 @ 7:00 pm

Rules and Regulations:

1. Each driver is required to fill out an entry form and provide their own combine, prepared in accordance with the rules and safety requirements of the event.
2. Derby officials may accept or reject any or all entries.
3. All combines must be inspected and approved by derby officials.
4. No radio communication with driver during the derby.
5. No alcohol is allowed in the pit area; Subject to disqualification.
6. No ganging up on a combine or group of combines; judges will disqualify upon their digression.
7. The decision of the judge and derby officials will be final.

Combine Unit:

1. The combine must be a 1985 model or older and con not be 4-wheel drive
2. Disconnect all drive belts to the threshing unit, grain table and straw chopper.
3. Fuel tank must be mounted inside the grain tank.
4. All combines must have a cab with seat belt installed.
5. All windows and glass must be removed from unit, including all lights.
6. Remove unloading auger from the grain tank.
7. No reinforcement plated of shields can be added to protect wheels and tires.
8. One or two bars may be added to protect the drive belts.
9. Must have a bar welded on each side of the cab to protect driver.
10. Must have a 2 foot wide piece of metal or wood in front of the cab to protect driver's feet.
11. No additional weight is to be added to the unit.
12. Tires are to be stock and nothing but air is to be used to inflate them.
13. No duals wheels allowed
14. There will be no concrete allowed to be used on the unit.

Header Unit:

1. A grain table must be used during the derby. No corn heads and No heads longer than 15 feet.
2. If head is removed during the derby then you will be disqualified; so weld it to the combine.
3. Remove reel, sickle bar, guards and floating cutter bar.
4. Head must be no lower than 15 inches or higher than 30 inches from the bottom of the head to the ground.
5. There can be no lift action on header from the cab; head should welded or fastened so it can not move up and down.